

# SBS 10

## ACTIVE SUBWOOFER WITH POWERED SPEAKER OUTPUTS

The SBS 10 features an integrated 10" low-frequency driver powered by a 160 W amplifier. It also includes two 60 W amplifiers for driving external satellite speakers. Audio input options include 100V line, balanced (XLR/TRS), and unbalanced (RCA) connections. A built-in EQ allows for treble and bass adjustment. The unit is protected against thermal overload, overcurrent, and output clipping, ensuring reliable performance in installed audio systems.



Technical Specifications	SBS 10
Rated output power	160 W subwoofer; 120 W external speakers amplifier
Subwoofer frequency response	20 Hz - 200 Hz
Speakers frequency response	20 Hz - 20 kHz
Crossover point	40 Hz - 200 Hz
Driver dimensions	10" (254 mm) woofer
Output impedance	8 $\Omega$
Equalizer center point (bass)	30 Hz $\pm$ 12 dBu
Equalizer center point (treble)	12 kHz $\pm$ 12 dBu
Dimensions	380 mm x 430 mm x 427 mm
Weight	17 kg
Material	Painted MDF
Colour	Black (RAL 9017)

# SBS 10

## ACTIVE SUBWOOFER WITH POWERED SPEAKER OUTPUTS

### Dimensions



430 mm



380 mm