

PUBLIC ADDRESS / SPEAKERS / CEILING

SKY-6T

6" CEILING LOUDSPEAKER WITH 100 V LINE TRANSFORMER



IP44


 SALT MIST
RESISTANCE

 3-POINT
ANCHORAGE


ANTI-DROP SYSTEM


 TAP-LOCK
TERMINALS

 TURN-LOCKABLE
GRILLE

- ✓ 6" double cone speaker. 15/10/5 W RMS@100 V
- ✓ Low profile aluminium grille
- ✓ Highly conductive quick-connect terminals
- ✓ Anti-fall system for installation assistance



+ Info:

<https://fonestar.com/SKY-6T>

ESPECIALLY RECOMMENDED IN:



Hospitality



Retail



Hotels



All sectors

DESCRIPTION

Pair of 6" double cone ceiling speakers. 15/10/5 W RMS@100 V. Low profile grille.

TECHNICAL CHARACTERISTICS

FEATURES	Ceiling loudspeaker with 100 V line transformer. Low profile frameless grille, constructed from rust resistant aluminium. Detachable, turn-lockable grille. The logo can be removed and painted. Fast connection terminals and high conductivity. Anti-fall system for installation assistance. Hook for safety cable. Stable, worm-gear ceiling brackets. Protection against dust and water.
POWER	15 W RMS 20 W MAX.
SPEAKER	6" polypropylene double cone diaphragm
RESPONSE	55-18,000 Hz @ -10 dB 85-18,000 Hz @ -3 dB
IMPEDANCE	15 W RMS@100 V (666 Ohm) 10 W RMS@100 V (1,000 Ohm) 7.5 W RMS@70V (666 Ohm) 5 W RMS@100 V/70 V (2,000 Ohm/1,000 Ohm) 2'5 W RMS@70 V (2,000 Ohm)
SENSITIVITY	88 dB @ 1 W/1 m
SOUND PRESSURE	97 dB @ max. W/1m Continuous 100 dB @ max. W/1m Peak
COVERAGE ANGLE:	150°@1kHz (-6 dB)
PROTECTIONS	IP-44 in compliance with IEC 60529 EN ISO 9227:2006 Neutral Salt Spray Test
MATERIAL	ABS (UV resistant) Liquid painted aluminium grille
CONNECTORS	Highly conductive quick-connect terminals For cable cross-section 0.4 ~ 4 mm².



+ Info:


<https://fonestar.com/SKY-6T>

OPERATION TEMPERATURE	-20°C ~ 70°C (48 h)
STORAGE TEMPERATURE	10°C ~ 40°C
MAXIMUM HUMIDITY	95%
COLOUR	White (RAL 9003)
DIMENSIONS	Total loudspeaker: 249 mm Ø x 85 mm height Grille section: 5 mm Recessed height: 80 mm Installation hole: 219 mm Ø Maximum ceiling thickness: 30 mm
WEIGHT	0.95 kg
ACCESSORIES	Installation template




+ Info:
<https://fonestar.com/SKY-6T>

SPL vs Frequency




SPL vs Angle



+ Info
<https://fonestar.com/SKY-6>

• Impedance vs Frequency



+ Info
<https://fonestar.com/SKY-6>