

PUBLIC ADDRESS / SPEAKERS / SURFACE

SONORA-5TN-EN

EN 54 SURFACE SPEAKER WITH 100 V LINE TRANSFORMER AND LOW IMPEDANCE



EN 54



IP66

SALT MIST
RESISTANCE

- ✓ Excellent sound quality
- ✓ Excellent finish and elegant design
- ✓ EN 54-24 certificate
- ✓ Prepared for outdoor use, protection against water and anti-corrosion materials.



+ Info:

<https://fonestar.com/SONORA-5TN-EN>

ESPECIALLY RECOMMENDED IN:



Hospitality



Education



Hotels



All sectors

DESCRIPTION

Loudspeaker for voice alarm systems EN 54. 40/20/10/5 W RMS@100 V. 40 W RMS@8Ohm. IP-66 protection and salt fog. Adjustable fixing mount. Steel safety cable.

TECHNICAL CHARACTERISTICS

FEATURES	Loudspeaker for voice alarm systems EN 54 Low-impedance loudspeaker with 100 V line transformer. Prepared for outdoor use, waterproof and rustproof materials.
INTENDED USE	Loudspeaker for voice alarm systems
STANDARDS	EN 54-24 certified Fire detection and fire alarm systems - Part 24: components of voice alarm systems - Loudspeakers EN 54-24: 2008
POWER	80 W max., 40 W RMS
LOUDSPEAKERS	1 x 5 1/4" woofer 1 x 1" tweeter
RESPONSE	80-20,000 Hz
IMPEDANCE	40 W RMS@100 V (250 Ohm) 20 W RMS@100 V/70 V (500 Ohm/245 Ohm) 10 W RMS@100 V/70 V (1.000 Ohm/490 Ohm) 5 W RMS@100 V/70 V (2.000 Ohm/980 Ohm) 2'5 W RMS@70 V (1.960 Ohm) Low Z: 8 Ohm
SENSITIVITY	86 dB @ 1 W/1 m 74 dB @ 1 W/4 m
MAXIMUM SOUND PRESSURE	99 dB @ max. W/1 m 89 dB @ max. W/4 m
COVERAGE ANGLE	135° H x 135° V @1kHz (-6 dB)
PROTECTION	Type B (EN 54-24) IP-66 in compliance with EN 60529 IEC 60068-2-11 Enviromental tests (Salt mist)
MATERIAL	ABS 5VB (UV resistance) Aluminium mesh grille with powder-coated finish Weather-resistant mount A2 stainless steel screws



+ Info:


<https://fonestar.com/SONORA-5TN-EN>

SWITCH	W selector in high Z and low Z
CONNECTORS	Euroblock in and out for cable 0.25 – 2.5 mm ² cross section
TEMPERATURE RANGE	–25°C ~ 70°C
COLOUR	Black (RAL 9005)
DIMENSIONS	Loudspeaker: 162 x 263 x 147 mm depth Mount wall plate: 68 x 110 mm Loudspeaker with mount: 216 mm depth
WEIGHT	2.2 kg
ACCESSORIES	Adjustable fixing mountt ± 60° in all directions. Steel safety cable



+ Info:

<https://fonestar.com/SONORA-5TN-EN>



FONESTAR	Model	Description	Units	Scale
	SONORA-5TN-EN	HANGING SPEAKER WITH 100 V LINE TRANSFORMER AND LOW IMPEDANCE IN COMPLIANCE WITH EN 54	mm	1:3